

MOISTURE GUARD®

ICE & RAIN UNDERLAYMENT

PRODUCT DATA



MANUFACTURED IN JOPLIN, MO

IMPORTANT SAFETY INFORMATION: Use personal fall protection devices when working on a roof. Personal fall protection devices, safety glasses and hearing protection must always be used when applying Moisture Guard underlayment. Moisture, frost or debris will decrease the traction when walking on Moisture Guard underlayment. **Applicator safety is of utmost importance.**

MOISTURE GUARD underlayment is a self-adhering, fiberglass and modified bitumen underlayment with a mineral surfacing, a removable release film on the adhesive side and removable selvedge release tape.

USES: For use as a self-adhering underlayment prior to installation of the final roof system and as a secondary layer used in areas susceptible to wind blown rain and ice damming. Moisture Guard is used on roof decks, along rake and eave edges, valleys and ridges, and around chimneys, dormers, vents and skylights. Moisture Guard is used under most types of roofing, including tile, wood shake, asphalt, slate or composite shingles. It is not recommended for use under metal roofing.*

- Self-adhering rubberized asphalt
- Mineral surfacing
- Fiberglass mat
- Split treated release film
- Selvedge release tape
- 5-Year Limited Warranty**

Underlayment products begin to age as soon as they are exposed to nature. Buildings experience aging factors differently, so it is difficult to predict how long a product will last. That's why TAMKO provides a Limited Warranty on Moisture Guard. Go to tamko.com for details or call us at 1-800-641-4691.

* Use TAMKO TW Metal & Tile Underlayment or TW Underlayment for metal roofing applications.

** See complete TAMKO Waterproofing, Fenestration Flashings, Underlayments and Accessories Limited Warranty at tamko.com for details.

CERTIFICATIONS

UL Classified as a Prepared Roofing Accessory

Moisture Guard has been tested by an independent laboratory for compliance with ASTM D1970-15

LIMITATIONS

- Underlayment must not be applied to wet or frosty surfaces.
- Underlayment should not be applied to unclean or contaminated surfaces.
- Underlayment must not come into contact with products containing coal-tar pitch.
- Best applied at temperatures of 35° F and higher.
- Once applied, underlayment must not be left exposed beyond 90 days.

PRODUCT DATA†

	0.87 Sales Square Roll	1.74 Sales Square Roll
Roll Dimensions	36" x 32'3"	36" x 64'6"
Roll Coverage††	87.34 sq. ft. (± 1.52 sq. ft.)	174.69 sq. ft. (±1.52 sq. ft.)
Roll Contains	96.75 sq. ft. (± 1.68 sq. ft.)	193.5 sq. ft. (±1.68 sq. ft.)
Thickness	55 mils	55 mils
Rolls Per Pallet	42	25
Pallet Size	37" x 47"	37" x 47"

† All values stated as nominal. †† When applied according to instructions.

Information included in this product data sheet was current at time of printing. To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

TAMKO Logo, Moisture Guard®, and TAMKO® are registered trademarks of TAMKO® Building Products, Inc.

